



## Standard Specifications



All of our homes are  
**ENERGY STAR**  
Plant Certified.

### Floor Systems

- Floor joist- 2x10 at 16" O.C. with 2 x 10 double perimeter band (24' – 28' wide modules)
- Floor joist- 2x10 at 12" O.C. with 2 x 10 double perimeter band (32' wide modules)
- 3/4" tongue and groove O.S.B. sub-floor glued and nailed decking
- All floors constructed with solid wood bridging

### Walls

- 2x6 – 16" O.C. exterior wall construction with R-19 fiberglass insulation
- 2x4 – 16" O.C. interior partition walls
- 2x4 marriage wall 16" O.C. with 7/16" OSB sheathing
- 7/16" O.S.B. exterior wall sheathing, glued and nailed with steel reinforcing over openings
- Smooth finish 1/2" Drywall (glued and screwed) interior walls with 2 coats of primer paint applied
- Solid headers with O.S.B. reinforcement
- R-19 Fiberglass exterior wall insulation with vapor barrier

### Roof and Ceiling

- 7/12 truss roof system at 16" O.C. (gable end walls and porches to match roof spacing)
- 7/16" O.S.B. roof sheathing
- Minimum 15# underlayment with self-sealing 30 year warranty Owens Corning architectural shingles
- R-38 Fiberglass ceiling insulation with vapor barrier
- 1/2" High-density drywall on ceilings fully taped and smooth finished drywall joints, including wall-ceiling joint
- 8' ceiling height; 9' ceilings are available, 10' also available in most areas per D.O.T. approval
- Shingle over rolled ridge venting
- 12" Eave overhangs with 6" aluminum fascia and vinyl vented soffit
- 12" Gable overhangs with 6" soffit and fascia
- Ice shield installed on eave overhangs
- Aluminum drip edge installed

### Cape Cods

- 2x4 studs at 16" O.C. on mating walls with 7/16" OSB sheathing
- 12/12 Roof system 16" O.C. with 2x10 floor joists and 1/2" high density ceiling drywall on first floor
- R-30 Fiberglass ceiling insulation between first and second floor, second floor unfinished
- 3/4" O.S.B. floor decking between kneewalls on second floor
- 2 Gable end windows (shipped loose)
- Roughed-in plumbing and electrical stubbed up to second floor for future on-site bath and living area
- Close-off package, which includes one 30" door, trim, studs, and drywall (shipped loose)
- Stairs to second floor installed -carpet grade (railing optional) \*Other stair tread/risers available

### Two Stories- First floor ceiling

- 2x4 studs at 16" O.C. on mating walls with 7/16" OSB sheathing
- 2856 windows throughout first floor (except kitchen and bath)
- 2852 windows throughout second floor (except bath)
- Insulation installed around perimeter between floor and ceiling
- All water and drain lines run on second floor with floor sheathing left off for connections to first floor
- All second story siding shipped loose
- Stairs to second floor installed- carpet grade (railing optional) \*Other stair tread/risers available
- Plumbing and electrical chase included

### Interior

- Interior white colonial six panel hollow core doors with 3 mortised hinges
- Colonial trim (2 1/2" doors and windows) – (3 1/2" base) pre-finished white. Light or medium stain available
- Lever style brushed nickel or polished brass lock sets (your choice in finish)
- White, open mesh wire closet shelving
- Wood jambs and colonial moldings at all openings including bi-fold and bypass door openings
- High quality paint for easy touch-up (2 prime coats only)
- Brushed nickel or bright brass passage and privacy interior door knobs and hinges

\*\*All Specifications are subject to change without notice.

\*\*Specs may be changed to suit your individual requirements.

#### Exterior

- Therma-Tru Smooth Star fiberglass 6 panel front door with viewer, knocker, and deadbolt
- Therma-Tru Smooth Star fiberglass 9-lite rear door or 6' vinyl patio door in rear as plan dictates
- Certainteed Mainstreet Premium Grade vinyl siding over 7/16" O.S.B. exterior wall sheathing with white J-channel and undersill. (If terratone windows, all trim will match siding.) Double 4 and German Lap all standard
- Front and rear door chimes (2 locations)
- Raised panel shutters included on front (shutters optional on contemporary designs)
- Andersen Silver Line 3000/3900 Double Hung trimmed vinyl tilt-sash windows with sills and screens (LoE<sup>2</sup> glass). Grilles are standard. **Meets or exceeds Energy Star compliance for all zones.**
- House wrap

#### Plumbing

- Single Lever faucets in kitchen and baths
- Copper water lines where required by code (no lead solder)
- Shut-off valves on each fixture
- PVC drain, waste, and vent system
- 2" future vent for all basement models
- Connection for washer and dryer as plan dictates, where applicable
- All washer hookups to have overflow pan
- PEX fresh water lines available

#### Electrical

- 200 AMP main service panel box with 40 breaker capacity
- Two exterior weatherproof receptacles with ground fault interrupter
- GFI protection on receptacles at kitchen and bath sink(s)
- AC/DC smoke detectors – per code
- Ceiling lights in kitchen, bath, hall, foyer, and stairwells \*Note- prep only for open foyer and dining room light fixtures
- Silent decorator rocker switches
- 220V Range outlet wired to panel box
- Two telephone jacks- CAT5
- Dryer Receptacle, per plan
- Energy gaskets on all outlets and switch boxes located on exterior walls
- Two RG6 TV jacks
- Switched bedroom receptacle
- Additional 2" electrical conduit for future expansion
- Lighting package

Heating- To be completed on site by Owner/Builder

#### Kitchen

- Quality Merillat Seneca Ridge Oak, raised panel, arched cabinets with roll out base shelves (except sink base) in 4 finish choices
- Beveled edge high pressure laminate countertop with backsplash.
- Deep 8" stainless steel sink with single lever faucet and spray. Single bowl available.
- Dishwasher- wired and plumbed for onsite Energy Star rated appliance installation
- Crown moulding at open soffit
- 30" color coordinated range hood
- Wire and plug for your on-site electric range
- Plumb and box for on-site icemaker

#### Bath

- 60" one-piece fiberglass tub/shower combination
- One piece fiberglass showers (floor plan dictates) with tempered glass doors, chrome
- Anti-scald valves in tubs and showers
- Elongated 1.6 gallon low flow water closet
- Vanity cabinets to match kitchen cabinets
- Kerrico cultured marble top with oval bowl with single lever faucet
- Combination fan/light ventilation unit
- Plate glass mirrors with decorative lights and side recessed medicine cabinet as plan allows
- Single lever faucets throughout
- Towel bar and toilet paper holder installed

#### Insulation

- Ceiling- R-38 with vapor barrier
- Exterior walls- R-19 fiberglass

\*\*All Specifications are subject to change without notice.

\*\*Specs may be changed to suit your individual requirements.